

	<p><b>TT level 1.1</b> Record Player</p> <p>0–33–45 RPM electronic switchable Incl. Tone arm, Audio Technica 3600L cartridge, cover, record weight Base in <b>transparent</b> acrylic of <b>black</b> acrylic WxDxH 430 x 327 x 140 mm, 8 Kg</p>	1.295,-
	<p><b>TT level 2.1 DC</b> Record Player including Speedpod</p> <p>0–33–45 RPM, control and fine adjustment via SpeedPod Incl. SpeedPod, tone arm, Audio Technica 3600L cartridge, cover, record weight Base in <b>transparent</b> acrylic of <b>black</b> acrylic WxDxH 430 x 327 x 152-162 mm, 8 Kg</p>	1.695,-
	<p><b>TT level 3.1</b> Record Player, BlackAcrylic/solid wood SpeedPod option: Speed adjustment in 0.01 rpm steps</p> <p>0–33–45 RPM, SpeedPod available as extra Incl Titanium tone arm, Audio Technica 3600L cartridge, cover, record weight Base in solid <b>beech</b> and black acrylic or solid <b>walnut</b> and black acrylic WxDxH 430 x 327 x 156 mm, 11 Kg</p>	2.495,- 199,-
	<p><b>Aka MC</b></p> <p>Aluminium cantilever / Bonded Tiny Spherical 5/20uM . Square coil 4N OCC, impedance 5 ohm, Bandwidth 20-20.000Hz +/-2dB Output level 0.3mV, Channel separation &gt; 24dB, Channel balance &lt; 0.8dB Tracking force 1.4-2.2 gram, recommended force 1.8 gram, VTA20 degrees Compliance 16 uM/mN, Weight 9 grams, recommended load 100-470 ohm</p>	395,-
	<p><b>Kuro MC</b></p> <p>Boron cantilever / Nude Eliptical 6/15uM Square coil 4N OCC, impedance 5 ohm, Bandwidth 20-22.000Hz +/-2dB Output level 0.26mV, Channel separation &gt; 25dB, Channel balance &lt; 0.5dB Tracking force 1.6-2.2 gram, recommended force 1.8 gram, VTA20 degrees Compliance 13 uM/mN, Weight 9 grams, recommended load 100-470 ohm</p>	795,-
	<p><b>Shiro MC</b></p> <p>Boron cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 20-25.000Hz +/-2dB Output level 0.26mV, Channel separation &gt; 26dB, Channel balance &lt; 0.3dB Tracking force 1.6-2.2 gram, recommended force 1.8 gram, VTA20 degrees Compliance 13 uM/mN, Weight 9 grams, recommended load 100-330 ohm</p>	1.295,-
	<p><b>Kin MC</b></p> <p>Ruby cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 15-25.000Hz +/-2dB Output level 0.28mV, Channel separation &gt; 28dB, Channel balance &lt; 0.3dB Tracking force 1.6-2.0 gram, recommended force 1.8 gram, VTA20 degrees Compliance 15 uM/mN, Weight 9 grams, recommended load 100-330 ohm</p>	1.795,-
	<p><b>Myo MC</b></p> <p>Saphire cantilever / Nude Fine Eliptical 5/15uM Square coil 6N OCC, impedance 4.7 ohm, Bandwidth 15-28.000Hz +/-2dB Output level 0.28mV, Channel separation &gt; 28dB, Channel balance &lt; 0.3dB Tracking force 1.3-2.0 gram, recommended force 1.8 gram, VTA20 degrees Compliance 16 uM/mN, Weight 9 grams, recommended load 100-330 ohm</p>	2.495,-

Retail prices in **Euro** including VAT, December 2025

<b>Aka</b>	Tak-aka	8721161341086
<b>Kuro</b>	Tak-kuro	8721161341093
<b>Shiro</b>	Tak-shiro	8721161341109
<b>Kin</b>	Tak-kin	8721161341116
<b>Myo</b>	Tak-myo	8721161341123